Repro Print 6M With Paper Cassette Tray

2 Media Roll Capacity

Advanced Integrated Auto A0/A1 Size Paper Cassette to Address Growing Need for Colored/ Preprinted Media

Integrated Color Scanner With RTT Technology

600 x 2400 DPI High Definition Printing Technology

Single Footprint Configuration

ISO-14000 Compliant

Repro Print 6M Precision Design

The Repro Print 6M delivers fast and accurate copies and prints using toner based imaging technology that produces UV stable prints. 100% toner efficient High Definition Print Technology ensures rich blacks and smooth gradients. Superior print, copy and scan resolution captures fine details with remark-able tone clarity, keeping reproductions true.

Premier Performance & Quality
Smart Eco2 Design
Color Touch Controls
High Definition Print Technology
100% Toner Efficient- Zero Waste
Energy Star Qualified System
Recycled Paper Approved
Components 97% Recyclable

Repro Print 6M System Expandability

The Repro Print 6M provides operators with the flexibility to direct prints and copies to a preferred output destination - the integrated top stacking system and/or to an optional rear stacking system for increased production. Repro print 6M systems deliver the best of both worlds: walk up convenience and production printing !

High Definition Printing

Printer Specification Repro Print 6M With Paper Cassette Tray

Technology	Monochrome LED, with HDP printing resulting in zero toner waste. Organic Photoconductor Drum
Resoluton	600 x 2400 DPI, 300 Lines per inch
Productivity	
Print Speed	6 meter per minute / 4 A0 per minute
Output Size Width	A4 - A0 (36"), 3" core dia
Warm Up time	Instant from stand by < 4.0 min from start up
Multiple media support	Print from USB
Media Source	Automatic 2 roll with media bypass. Advanced Integrated Auto A0/A1 Size Paper Cassette to Address Growing Need for Colored/Preprinted Media
Media Types	Bond, Vellum. Translucent Bond, Film (compatble with recycled & colored bond)
Controller	
Ram	1 GB upgradeable to 16GB
Hard disc	320Gb upgradeable to 1 TB
Printable formats	
Vector	HPGL/2 formats(.plt,.hpg,.gl2, .000,.rtl,.906,.907,etc.), HPGL formats, HP-RTL formats, Autodesk DWF (.dwf) **Optional Formats** Adobe Portable Document Format (.pdf)*, Postscript (.ps)*, Encapsulated Postscript (.eps)*
Operator Interface	
Screen	15.6 inch full colour, long life Multi-Touch display for all operations
Preview	Real time image preview of all scanning and copying
Printer Weight	244kg
Network	1 x RJ45 port, CAT5 100/1000mb
Atmospheric requirements- Temperature Humidity	10-32^{o}C 15-85% non condensing
Energy consumption	**Printing Mode** 1,500W, **Standby Mode** <14W , **Energy star sleep mode** 6.34W

Scanner Specificaation

Type	CIS scanner with RTT Technology
Resoluton	600 DPI
Original feed	Face up
Original width	257-914mm
Original thickness	0.05-1.6mm
Colour mode	Monochrome – Binary, Greyscale – 4 bit / 8 bit, Colour 24 bit (Color scan optional)
Scanning speed	Monochrome 200 DPI = 250mm/sec, Colour 200 DPI = 82mm/sec
Mono Copying/Scanning	
Input selection	Line, Line/photo, Photo, Manual, despeckle, background removal
Output selection	Draft, Normal, Quality
Set copy	Up to 999 sets of 999 copies Test set (concurrent print)
Edit set	Change order, Add image, Delete image, Zoom to view
View last job	Recall last job for editing of print parameters and reprintng
Stamping	Select from predetermined set of stamps
Zoom	5%-400% in 0.1% increments, Zoom to paper size, A size to A size, A size to b Size, Preset rato
Recall Last Job	Recall edit parameters and resubmit
Standalone Functon without PC or Network	Scan directly to USB Drive, Print Directly from USB Drive

*All product features and specifications are subject to change without notice